



Features

- **Din Rail/ Screw Mounting Dual Purpose**
- **Convection cooled**
- **Wide input range**
- **100% burn-in test**
- **MOSFET designed**
- **1 year Warranty**
- **Output modify range: 3V~200VDC**

DIMENSIONS : 104(H) x 76(D) x 45(W)mm
WEIGHTS: 230g



General specifications

INPUT

Input range 180~264VAC
 200~380VDC
Input frequency 47~63Hz
Inrush current (25° C) 40A/220VAC

OUTPUT

Hold-up time 13mS
Short protection Autorecovery

Detail specifications

40~50 Watts

MODEL	O/P Volt Adj. ± %	Load(Current) ¹			Ripple & Noise ⁴	Line REG. ²	Load REG. ³	Efficiency ⁵
		Min.	Rated	Max.				
LP1040D-5	V1: +5V ±10%	0A	8.0A	8.0A	50mVp-p	±1%	±1%	78% Min.
LP1050D-12	V1: +12V ±10%	0A	4.2A	4.2A	100mVp-p	±1%	±1%	81% Min.
LP1050D-24	V1: +24V ±10%	0A	2.1A	2.1A	240mVp-p	±1%	±1%	81% Min.

Environments

Operating Temperature -15 ~ 50°C, Ambient
Operating Humidity 5 ~ 95% RH, No Condensing
Storage Temperature -20 ~ 85°C, Ambient
Vibration 2G, 10~500Hz, 3 axes

- NOTE:**
1. Each output can provide up to maximum load, but total load can not exceed rated output power.
 2. Line regulation is measured from low line to high line at rated load.
 3. Load regulation is measured from 20% to 100% of rated load at 110VAC input.
 4. Ripple & Noise is measured by using a 0.1uF/630V metalized capacitor & a 47uF electrolytic capacitor parallel on the test point, at rated load and 110VAC input.
 5. Efficiency is measured at rated load and 110VAC input.
 6. Hold-up time is measured at rated load and 110VAC input.

All Specifications be retained the right to modify by Reign Power

WEB : <http://www.switching-powers.com>
E-mail : rp21003f@ms7.hinet.net

Tel : 886-2-22997550
Fax : 886-2-22997596

REIGNPOWER
S.M.P.S